

Woven geogrid for reinforcement of asphalt pavements



Woven geogrid from high tenacity PET yarns additionally dipped by acrylate dispersion

Product designation			20/20	40/40	50/50	60/60	80/80	100/100
Tensile strength	MD	kN/m	25	45	55	70	90	110
	tolerance		-5	-5	-5	-10	-10	-10
<i>EN ISO 10319</i>	CMD	kN/m	25	45	55	70	90	110
	tolerance		-5	-5	-5	-10	-10	-10
Elongation at break	MD	%	12,5	12,5	12,5	13	13	14,5
	tolerance		± 2,5	± 2,5	± 2,5	± 2,5	± 2,5	± 2,5
<i>EN ISO 10319</i>	CMD	%	12,5	12,5	12,5	13	13	14,5
	tolerance		± 2,5	± 2,5	± 2,5	± 2,5	± 2,5	± 2,5
Mesh Size (standard)	mm	20 x 20 or 35 x 35						
Form of supply		rolls						
Width (standard)	m	3,4						
Length (standard)	m	100						
Area	m ²	340						

Description

Armatex® is a woven geogrid, made of high tenacity PET yarns additionally dipped by acrylate dispersion, for reinforcing surfaces made of bitumen. Rolls can be placed on the open air and piled up max. into 5 layers. Keep out of reach fire! Rolls can be transported by truck, train or in containers.

Kordárna Company is capable of designing and manufacturing product precisely as per requirements. The values given are indicative and correspond to average results obtained in our laboratories and in testing institutes. The right is reserved to make changes without notice at any time.



Kordtrade, s.r.o.
Velká nad Veličkou 890
696 74 Czech Republic
www.kordarna.cz