

Woven geotextiles made from high tenacity PET yarns

| Product designation | | | 100/200 | 100/300 | 100/400 |
|----------------------------|-----|------|--------------------------|---------|---------|
| Tensile strength | MD | kN/m | 110 | 110 | 110 |
| tolerance | | | -10 | -10 | -10 |
| <i>EN ISO 10319</i> | CMD | kN/m | 220 | 330 | 440 |
| tolerance | | | -20 | -30 | -40 |
| Elongation at break | MD | % | 10 | 10 | 10 |
| tolerance | | | ±2 | ±3 | ±3 |
| <i>EN ISO 10319</i> | CMD | % | 10 | 10 | 10 |
| tolerance | | | +/-2 | +/-3 | +/-3 |
| Form of supply | | | rolls | | |
| Diameter | m | | 0,6 - 1,25; standard 0,8 | | |
| Length (standard) | m | | 150 | | |

Description

Kortex[®] Tube is a woven geotextile, made of high tenacity PET and twisted on a circular loom. Rolls can be placed on the open air and piled up max. into 5 layers. Keep out of reach fire! Rolls can be transported by truck, train or in containers. Kordárna Company is capable of designing and manufacturing product precisely as per requirements. The values given are indicative and correspond to average results obtained in our laboratories and in testing institutes. The right is reserved to make changes without notice at any time.



KORDÁRNA
A MEMBER OF THE KORD GROUP



Kordtrade, s.r.o.
Velká nad Veličkou 890
696 74 Czech Republic
www.kordarna.cz